

```
<div class="articleTable"> <table border="0" cellspacing="0" cellpadding="0">   <tr> <td>  
valign="top"> <p align="center">MODEL</p> </td> <td valign="top"> <p  
align="center">EY-20B</p> </td> </tr> <tr> <td valign="top"> <p>Type</p> </td> <td  
valign="top"> <p align="center">Air-cooled, 4-cycle single cylinder, side valve, gasoline  
engine</p> </td> </tr> <tr> <td valign="top"> <p>Displacement◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆  
cm3</p> </td> <td valign="top"> <p align="center">183</p> </td> </tr> <tr> <td>  
valign="top"> <p>Maximum output◆◆◆◆◆◆◆ kW/rpm<br /> (HP/rpm)</p> </td> <td>  
valign="top"> <p align="center">3.73/2000<br /> (5.0/2000)</p> </td> </tr> <tr> <td>  
valign="top"> <p>Direction of Rotation</p> </td> <td valign="top"> <p  
align="center">Counterclockwise, as viewed from P.T.O. Shaft side</p> </td> </tr> <tr> <td>  
valign="top"> <p>Lubricant</p> </td> <td valign="top"> <p align="center">Class SC or higher  
grade, SAE #20, #30, #40</p> </td> </tr> <tr> <td valign="top"> <p>Fuel</p> </td> <td>  
valign="top"> <p align="center">Automotive Gasoline (Unleaded)</p> </td> </tr> <tr> <td>  
valign="top"> <p>Fuel Tank Capacity◆◆◆◆ Liter</p> </td> <td valign="top"> <p  
align="center">3.8</p> </td> </tr> <tr> <td valign="top"> <p>Spark plug</p> </td> <td>  
valign="top"> <p align="center">NGK B-6HS or BR-6HS, (CHAMPION L86C)/NGK  
BR6HS</p> </td> </tr> <tr> <td valign="top"> <p>Starting system</p> </td> <td>  
valign="top"> <p align="center">Recoil starter</p> </td> </tr> <tr> <td valign="top"> <p>Dry  
weight◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆ Kg</p> </td> <td valign="top"> <p  
align="center">16.0</p> </td> </tr> <tr> <td valign="top"> <p>Dimensions (LxWxH)mm</p>  
/<td> <td valign="top"> <p align="center">324x318x325x392</p> </td> </tr> </table> </div>
```